



Granville Minerva SHPD 60 15W/40

25 Litre & 205 Litre

Product Description

Granville Minerva SHPD 60 15W/40 meets a variety of requirements of European engine manufacturers in both normally aspirated and turbo engines working under difficult conditions, with extended drain period up to 60,000 kms (subject to specified operating conditions). Suitable for EURO 2 engines.

Recommended for use by Granville for the following manufacturer's specifications

API: CH-4
MAN: 3275
Volvo: VDS-2
MTU Type 2
ACEA: E5
MB: 228.3



* Image for illustrative purposes only.

Size	Part No	Barcode
25 Litre	3520D	5020618035206
205 Litre	3521B	5020618035213

Product Benefits

- * Outstanding performance and protection
- * Effective emission control

Product Usage

For engines where this specification lubricant is required.

Directions for Use

As recommended by the engine manufacturer.

Storage Instructions

Keep sealed in a cool, dry place.

Shelf Life

5 years from date of manufacture.

Appearance	:	Amber liquid
Odour	:	Characteristic
Specific Gravity	:	0.874 @ 15.6°C (typical)
Solubility	:	Insoluble in water
Flashpoint	:	>200°C
Kinematic Viscosity @ 40°C	:	105.44 cSt typical)

Revision: 1 | Date: 20/03/2012





Granville Minerva SHPD 60 15W/40

25 Litre & 205 Litre

Kinematic Viscosity @ 100°C : 14.49 cSt (typical)

Safety Precautions

Please see our latest EC Safety Data Sheets for details.

Transport Classification

Please see our latest EC Safety Data Sheets for details.

Quality Lubricants

Quality Lubricants

Quality Lubricants

** The information contained in this leaflet is provided to enable the user to assess the product and should not be taken as a specification. All information provided is given in good faith, we can however not assume liability. It is up to the user to ensure that the information and the product is suitable for the use intended.*

Revision: 1 | Date: 20/03/2012

